Study of EMG-based Mouse Clicks Type Detection

Romy Budhi Widodo Human-Machine Interaction Research Centre, Informatics Engineering, Universitas Ma Chung Malang, Indonesia romy.budhi@machung.ac.id Devina Trixie Human-Machine Interaction Research Centre, Informatics Engineering, Universitas Ma Chung Malang, Indonesia Windra Swastika Artificial Intelligence for Digital Image and Technopreneurship, Informatics Engineering, Universitas Ma Chung Malang, Indonesia

Abstract— The operation of a computer required humans to use several parts of their body. However, there were some conditions where humans cannot operate computers correctly or in a normal position; examples of these conditions were accident victims and people with disabilities. Therefore, a system was needed to help make it easier for these people to operate the computer. This study developed a system that can classify click types using EMG sensors, the K-NN method, and the SVM method. EMG sensors helped take data in the form of signals from human muscle contractions which will later be classified into left-click and right-click. At the same time, it was useful for classifying these types of clicks for the K-NN and SVM methods. Data from EMG sensors were trained using the K-NN and SVM methods using 54 data sets in each class, namely leftclick and right-click classes. The K-NN method was trained using k=3, 5, 7, 9, and 11. The SVM method used linear kernels, Radial Basis Function (RBF), polynomials, and sigmoids. After that, the accuracy values of the two methods will be compared. The study has successfully classified the types of clicks based on the input from the EMG sensor using the K-NN method with the highest accuracy results using k=3, which was 81.81%, and the SVM method using polynomial kernels which were 84.84%. The highest accuracy value was obtained by comparing the two methods, namely using the polynomial kernel SVM method. Adding datasets and conducting experiments using other methods as further comparisons can be used to improve system accuracy.

Keywords— EMG, K-Nearest Neighbor, Support Vector Machine (SVM), classification

I. INTRODUCTION

Traffic accidents are unforeseeable and are very much avoided by everyone. This incident involves a vehicle with or without another motorist, which can result in human casualties from only minor injuries, severe injuries, and even death. Some victims of these accidents have jobs they cannot leave behind, one example of which is those who have to operate a computer. Accident victims who have suffered severe injuries such as permanent fractures or cannot sit in a normal position have difficulty operating the computer to the fullest. In addition to victims of traffic accidents, some people have difficulty operating computers, that is, people with disabilities.

A person with a disability is any person who experiences physical, intellectual, or mental. Sensory limitations, and who interact with the environment may experience obstacles and difficulties in participating fully and effectively with others based on equal rights. For example, instead of working physically, it would be better if they worked in front of a computer because it does not require a large amount of physical exertion. To operate a computer, a mouse is a critical apparatus. The purpose of the computer mouse is to move the cursor to a particular icon/shortcut, left-clicking to access a file, right-clicking to open additional menus, and many others. However, not all people with disabilities can operate the mouse optimally due to its limitations.

Not inferior to the development of smartphones that are currently rampant, computer technology also continues to develop. On computer devices, there have begun to be several tools or applications to help people with disabilities, such as speech recognition, typing robots, mice shaped like gloves installed to drive pointing devices, and so on.

In previous research [1]–[3], a prototype of a pointing device using Electromyography and a bend sensor is employed as clicking input. The completed click detector is to detect left clicks only. Based on previous researchers' advice, developing a prototype or an EMG sensor is advisable because the EMG sensor is more comfortable to wear and expends less effort than using a bending sensor.

There have been several previous studies, namely research using a combination of foot switches and low-cost Inertial Measurement Units (IMU) for mice that can be used in human and computer interaction. In this study, the clicks used were to use feet. As a result, this study has a good throughput (TP) and movement time, namely TP=1.37 bps. However, the device in this study still provides a reasonably heavy load for the user's neck [4]. The second study used IMU and bending sensor as a pointing device and click method, but this study only used the left click. As a result, this study has better results with TP = 1.75 bps. However, the device used also has shortcomings in comfort [4]. The latter is a study of mice using an android-based upper arm and an ANN that uses hand gestures as click markers. In this study, two gestures were compared, and obtained throughput and movement time results of 0.19 bps and 22.18 s for gesture 1 and 0.19 bps and 22.66 s for gesture 2. Comparing the two gestures showed that gesture one is more comfortable has a low level of fatigue, and is more effective than gesture 2 [5]. However, the research still does not include the convenient click feature on the mouse, which is one of the important features in computer operation.

Electromyograph (EMG) sensor is a unique tool from biosignalplux. The results of the EMG sensor will be classified into two classes, namely, left-click, and right-click.

II. RELATED STUDIES

A. Electromyography (EMG)

Electromyography, commonly referred to as EMG, is the process of detecting, analyzing, and utilizing electrical signals derived from muscle contraction [6]–[9]. The tool used in this process is called an electromyograph. In contrast, the resulting signal is called an electromyogram or

myoelectric signal. EMG is widely used for the rehabilitation process of people with disabilities, either due to amputation or due to other causes such as stroke. EMG signals can be obtained in two ways, through electrode implantation (intramuscular EMG) and without electrode implantation in the patient's body (surface EMG). Intramuscular EMG uses a fine wire-shaped needle placed in the muscle, as shown in Fig. 1. The implanted electrodes provide a better and more direct signal from the desired muscle source [10]-[18]. However, the installation must go through surgical operations, so it is less preferred and avoided. Therefore, electrodes not planted or placed on the surface are more widely used. It is just that the signals obtained are not as good as those planted and are often influenced by signals from the surrounding muscles. The method of electrodes placed on the surface, commonly called Surface EMG is a technique in which electrodes are placed on the skin on top of the muscles to detect electrical activity in the muscles. The installation of the surface EMG can be seen in Fig. 2.



Fig. 1. Intramuscular EMG



Fig. 2. Surface EMG

B. Support Vector Machine (SVM)

The Support Vector Machine (SVM) was developed by Boser, Guyon, and Vapnik and first presented in 1992 at the Annual Workshop on Computational Learning Theory. SVM is a machine learning method that works on the principle of Structural Risk Minimization (SRM), intending to find the best hyperplane that separates two classes in input space [19]. According to Vapnik and Cortes [20], a Support Vector is a machine-learning classification method for two groups. The hyperplane is a function that can be used to separate between classes. The best hyperplane can be found by measuring the margin and looking for its maximum point. Margin is the distance between the hyperplane and the pattern or the nearest outermost object of each class. In SVM, the outermost data object closest to the hyperplane is called the support vector. Support vectors are the most difficult to classify due to their almost overlapping position with other classes. Given its critical nature, only this support vector is considered to find the most optimal hyperplane by SVM.

The SVM algorithm uses a set of mathematical functions defined as kernels. The function of the kernel is to take data as input and convert it into the required form. Different SVM algorithms use different types of kernel functions. Examples of kernel function types in SVM are Linear, Nonlinear, Radial Basis Function (RBF), Sigmoid, and Polynomial.

Linear is the simplest SVM kernel. Linear kernels are commonly used when the analyzed data is already linearly separated. The equation of the linear kernel SVM is as in (1).

$$k(x, y) = x^T \cdot y \tag{1}$$

RBF kernel is a function commonly used in analysis when data is not linearly separated. RBF kernel has two parameters, namely Gamma and Cost. The Cost parameter, commonly referred to as C, works as SVM optimization to avoid misclassification in each sample in the training dataset. The Gamma parameter determines how far the influence of a single sample training dataset with a low-value meaning "far away" and a high-value meaning "near." With a low gamma, a point far from a reasonable dividing line is considered in the calculations for the dividing line. When high gamma means that the points are around, a good line will be considered in the calculation. The equation of the RBF kernel is as in (2).

$$k(x,y) = \exp\left(-\frac{\|x-y\|^2}{2\sigma^2}\right) \tag{2}$$

Sigmoid Kernel, also known as Hyperbolic Tangent Kernel and Multilayer Perceptron (MLP) Kernel. The Sigmoid kernel is derived from the Neural Network, where the bipolar function of the sigmoid is commonly used as an activation function for artificial neurons. The equation of the Sigmoid Kernel is as in (3).

$$k(x, y) = \tanh(\alpha x^T y + c)$$
(3)

Kernel polynomials are kernel functions used when data is not linearly separated. Kernel polynomials are well suited for problems where all training datasets are normalized. The equation of the Polynomial kernel is as in (4).

$$k(\boldsymbol{x}_i, \boldsymbol{x}_j) = (\boldsymbol{x}_i \cdot \boldsymbol{x}_j + 1)^2 \tag{4}$$

C. K-Nearest Neighbor

K-Nearest Neighbor, commonly called K-NN, is included in supervised learning, where the results of new instance queries are classified based on the majority of the proximity of the closest k-neighbors of the categories in K-NN. Supervised learning is an approach with already trained data and targeted variables. Hence, this approach aims to group data into existing data. The use of KNN for classification is very widely used by researchers [21]-[25].To use the K-NN algorithm, it is necessary to determine the number of k closest neighbors used to classify new data. The number k, preferably an odd number, for example, k = 1, 3, 5, and so on. The determination of the value of k is based on the amount of data present and the size of the dimensions formed by the data-the more data, the lower the number of k chosen. However, the more significant the dimension size of the data, the higher the k number is preferred. In simple terms, K-NN works based on the minimum distance from the new data to the training data to determine the K-nearest neighbor. The closest way to calculate the closest distance of the new data to its neighbors is to use the Euclidean Distance formula.

D. Feature Extraction

Feature extraction is a method that selects and combines variables into features, effectively reducing the amount of data to be processed while wholly and accurately describing the original data set.

1. Max EMG Value

Looks up the highest (maximum) value of the total number of samples used (1000 samples/second)

2. Min EMG Value

Looks up the lowest (minimal) value of the overall number of samples used (1000 samples/second)

3. Wave Length

Used to find the wavelength obtained by the EMG sensor, which will later be used as one of the classification features.

$$WL = \frac{1}{N} \sum_{i=1}^{n-1} |x_{i+1} - x_i|$$
(5)

4. Mean Absolute Deviation

$$MAD = \frac{\sum_{i=1}^{n} |x_i - \overline{x}|}{n}$$

Notes:

- \overline{x} : mean
- x_i : signal value

n : number of values

III. SYSTEM DESIGN

A. Needs Assessment

The device used for the detection of muscle contractions is the Biosignalsplux EMG sensor. There are three electrodes attached to the user's upper arm. One electrode acts as a reference or ground, which will be installed on the left shoulder, and the other two electrodes will be placed on the biceps muscle on the left arm. The data will be read using an application from Biosignalsplux called OpenSignals (r)evolution. The data read directly (real-time) in this application is in the form of a signal according to muscle contraction, then stored in the form of a .txt that can be transformed into a .csv form. The .csv data will later be used as input in two methods, K-NN and SVM, which have the output detected left-click or right-click. After learning each method, it will be compared to determine which is better. Finally, the output will be displayed on the computer screen with a click.

B. System Flow

The system's flow starts from the contraction of the muscles in the human upper arm to indicate a left or right click. Then the three electrodes will read the data and send the data to the EMG sensor. The data will be received by the Hub and transmitted to the computer using Bluetooth. The sensor will read the data in real-time. The data obtained will be processed by K-NN and SVM to be identified and classified into left-click and right-click. After that, it will be displayed on the screen with a click. When we can click, the computer will display the position of the pointer on the screen that can be used to run prototype tests with ISO 9241-411 assessment instruments. The EMG sensor will only function as a click; to move the cursor, another tool is needed, namely the mouse. The tests will produce data records containing accuracy data, errors, and so on that will be used for statistical data processing as a benchmark for the success rate of the prototype.



Fig. 3. Flow of System

C. Implementation

(6)

Next is the implementation of a pre-designed system. System creation is created with several programming languages that support the creation of this system. When implementing the system into a coding line, many things need to be considered and done to get good results. Improvements will continue to be made to get better results before proceeding with the testing phase. This system will be created with various software and programming languages as follows.

- a. Data: h5 file
- b. Programming language: Python 3.5.4
- c. Software: Opensignals

In addition, the hardware used to create and develop this system is as follows.

- a. Sensor: EMG Biosignalplux
- b. Operating system: Windows 10 Home 64-bit
- c. Processor: Intel(R) Core(TM) i5-7200U
- d. RAM: 8GB

D. Evaluation

The learning process of the K-NN and SVM methods is evaluated by conducting tests using a confusion matrix. Judgment from the accuracy results of each method. These two methods will also be compared to determine which has a higher accuracy value and a minor error and is better at classifying. Then the results of this study will be compared with previous studies with different tools but with the same accuracy calculation method. Finally, accuracy testing uses the value of accuracy, precision, recall, and f-measure

IV. RESULTS AND DISCUSSION

A. Data Collection Results

The data came from an EMG sensor affixed to the respondent's upper left arm. The dataset retrieval is retrieved using an application already provided by biosignalplux. The application can record the contraction results produced by the sensor, and the results obtained can be saved to become a dataset. An example of the data retrieval process can be seen in figure 3. The red box is contracted when doing a left click, the blue box contraction is for a right click, and the yellow box is for the no-click data.



Fig. 4. Example of Muscle Contraction Signal

The number of subjects is 9 (88% males and 12% females). The respondents' age range is 23-27 years, the weight is 48-98 kg, and the height is about 166-178 cm.

The results obtained from the muscle contraction record are exported into txt and h5 files. The result of resulting data can be seen in the txt file. Table 1 shows an example of muscle contraction data.

TABLE I. EXAMPLE OF SIGNAL CONTRACTIONS DA	ΤA
--	----

Sequence	EMG (mV)
0	32696
1	32732
2	32640
30031	42296
30032	43332
30033	43876
2 30031 30032 30033	32640 42296 43332 43876

Based on the analysis results from the data obtained, it can be seen that before the contraction, the resulting EMG results are stable at 32000. However, if there is a contraction, the EMG results will increase by approximately 37000–44000 according to the strong results of muscle contractions carried out by respondents. Each respondent has a different range of numbers because each respondent also has different muscle mass and fat.

As for the h5 file data results, the file will be used as a system input and processed as training data and testing data. In addition, H5 data can be read and processed faster by a computer. Therefore, the use of h5, which is focused on storing and processing data by computers, is the right choice to be used as a data source in making systems.

The initial process is to process the EMG results with a predetermined formula to obtain data on wavelength, mean absolute deviation, min value, and max value. Then, these four features will be used as training model input.

After the four features are successfully retrieved, the data still cannot be entered for training models. This is because data with different range variants will cause the results of one feature, especially those with a range that is too small from the others, not to have the same impact as other features with a more extensive range. Then the normalization of the Min-Max Scaler is carried out. After the normalization results, all existing features will be in the range of 0-1 so that each feature can contribute equally to the model training that will be carried out.

The dataset will be divided into 80% as training data, and the remaining 20% will be made into testing data. The initial datasets amounted to 54 data for each class, so it was divided into 43 data as training data and 11 as testing data for each existing class. The data amount is also equal to maximize system learning and accuracy value

B. Experiment Results

Testing using the K-NN method is carried out by trying the k parameter. The parameter k is worth an odd random number from values 3 to 11. Each k parameter value is tested to obtain the precision, recall, f1-score, and accuracy values. The following are the test results of each value of the k parameter. The first k-parameter experiment is 3, getting the value shown in Table II. The accuracy value obtained from k=3 is 81.81%.

TABLE II. KNN TEST RESULTS USING PARAMETER K = 3

	precision	recall	fl-score
No Click	0,83	0,91	0,87
Left Click	0,83	0,71	0,77
Right Click	0,78	0,88	0,82

The second experiment is with the parameter k valued at 5, getting the value specified in Table III. The accuracy value obtained from k = 5 is 78.78%.

TABLE III. KNN TEST RESULTS USING PARAMETER K = 5

	precision	recall	f1-score
No Click	0,82	0,82	0,82
Left Click	0,77	0,71	0,74
Right Click	0,78	0,88	0,82

The third experiment is with the parameter k worth 7, getting the value set in Table IV. The accuracy value obtained from k = 7 is 81.81%.

TABLE IV. KNN TEST RESULTS USING PARAMETER K = 7

	precision	recall	f1-score
No Click	0,82	0,82	0,82
Left Click	0,79	0,79	0,79
Right Click	0,88	0,88	0,88

The fourth experiment is with the parameter k worth 9, getting the value set out in Table V. The accuracy value obtained from k = 9 is 81.81%.

TABLE V. KNN TEST RESULTS USING PARAMETER K = 9

	precision	recall	fl-score
No Click	0,82	0,82	0,82
Left Click	0,79	0,79	0,79
Right Click	0,88	0,88	0,88

The fifth experiment is with the parameter k valued at 11, getting the value set out in Table VI. The accuracy value obtained from k = 11 is 81.81%.

TABLE VI. KNN TEST RESULTS USING PARAMETER K = 11

	precision	recall	fl-score
No Click	0,77	0,91	0,83
Left Click	0,83	0,71	0,77
Right Click	0,88	0,88	0,88

Based on the five k-parameter experiments that have been carried out, it can be concluded that the highest accuracy value is at the time k = 3, 7, 9, and 11, which is 81.81%. Because the highest accuracy value obtained is in the four k values, the most optimal k value will be taken using the smallest k value, namely k = 3.

Testing using the SVM method is done by trying four types of kernels. The kernels tested were Linear, Polynomial, RBF, and Sigmoid Kernels. Here are the test results of each kernel.

The first experiment was to use a linear kernel. In this experiment, we get the values as shown in Table VII. The accuracy value obtained from the linear kernel is 78.78%.

TABLE VII. SVM TESTING RESULTS USING LINEAR KERNELS

	precisio	recall	fl-score
	n		
No Click	0,71	0,91	0,80
Left Click	0,83	0,71	0,77
Right Click	0,86	0,75	0,80

The second experiment was to use a polynomial kernel. In this experiment, we get the values as shown in Table VIII. The accuracy value obtained from the polynomial kernel is 84.84%.

TABLE VIII. SVM TESTING RESULTS USING POLYNOMIAL KERNELS

	precision	recall	fl-score
No Click	0,77	0,91	0,83
Left Click	0,85	0,79	0,81
Right Click	1,00	0,88	0,93

The third experiment was to use the RBF kernel. In this experiment, we get the values as shown in Table IX. The accuracy value obtained from the RBF kernel is 78.78%.

TABLE IX. SVM TESTING RESULTS USING RBF KERNELS

	precision	recall	fl-score
No Click	0,77	0,91	0,83
Left Click	0,82	0,64	0,72
Right Click	0,78	0,88	0,82

The fourth experiment was to use the sigmoid kernel. In this experiment, we get the values as shown in Table X. The accuracy value obtained from the sigmoid kernel is 42.42%.

TABLE X. SVM TESTING RESULTS USING SIGMOID KERNELS

	precision	recall	fl-score
No Click	0,52	1,00	0,69
Left Click	0,00	0,00	0,00
Right Click	0,38	0,38	0,38

Based on the four kernel experiments that have been carried out, it can be concluded that the highest accuracy value is when using polynomial kernels, namely with an accuracy value of 84.84%.

REFERENCES

- R. B. Widodo, A. B. Haryasena, H. Setiawan, P. L. Tirma Irawan, M. Subianto, and C. Wada, "Design and evaluation of upper-arm mouse using inertial sensor for human-computer interaction," *J. Eng. Sci. Technol.*, vol. 15, no. 6, pp. 3673–3690, 2020.
- [2] B. Visser, M. P. De Looze, M. P. De Graaff, and J. H. Van Dieën, "Effect of precision demands and mental pressure on muscle activation and hand forces in computer mouse tasks," *Ergonomics*, vol. 47, no. 2, pp. 202–217, 2004, DOI: 10.1080/00140130310001617967.
- [3] K. Søgaard, H. B. Olsen, A. K. Blangsted, and G. Sjøgaard, "Single motor unit firing behavior in the right trapezius muscle during rapid movement of right or left index finger," *Front. Hum. Neurosci.*, vol. 8, no. November, pp. 1–9, 2014, DOI: 10.3389/fnhum.2014.00881.
- 8, no. November, pp. 1–9, 2014, DOI: 10.3389/fnhum.2014.00881.
 [4] R. B. Widodo *et al.*, "The IMU and Bend Sensor as a Pointing Device and Click Method," in *Proceedings - 2019 International Seminar on Intelligent Technology and Its Application, ISITIA 2019*, 2019, pp. 294–297, DOI: 10.1109/ISITIA.2019.8937086.
- [5] H. Sugihono, R. B. Widodo, and O. H. Kelana, "Study of the android and ANN-based upper-arm mouse," in *International Conference on Electrical Engineering, Computer Science and Informatics (EECSI)*, 2018, vol. 2018-Octob, pp. 718–723, DOI: 10.1109/EECSI.2018.8752895.
- [6] A. Krasoulis, S. Vijayakumar, and K. Nazarpour, "Multi-Grip Classification-Based Prosthesis Control with Two EMG-IMU Sensors," *IEEE Trans. Neural Syst. Rehabil. Eng.*, vol. 28, no. 2, pp. 508–518, 2020, doi: 10.1109/TNSRE.2019.2959243.
- [7] C. G. Pinheiro and A. O. Andrade, "The simulation of click and double-click through EMG signals," in *Proceedings of the Annual International Conference of the IEEE Engineering in Medicine and Biology Society, EMBS*, 2012, no. I, pp. 1984–1987, DOI: 10.1109/EMBC.2012.6346345.
- [8] K. Muthukumar and T. J. Jayan, "Examine the optimal position of controls and display in computer numerical control machines," *J. Eng. Res.*, vol. 9, pp. 1–16, 2021, DOI: 10.36909/jer.ICMMM.12357.
- [9] Y. Ding, Y. Cao, V. G. Duffy, and X. Zhang, "It is Time to Have Rest: How do Break Types Affect Muscular Activity and Perceived Discomfort During Prolonged Sitting Work," *Saf. Health Work*, vol. 11, no. 2, pp. 207–214, 2020, DOI: 10.1016/j.shaw.2020.03.008.
- [10] M. K. Jung et al., "Intranuscular EMG-Driven Musculoskeletal Modelling: Towards Implanted Muscle Interfacing in Spinal Cord Injury Patients," *IEEE Trans. Biomed. Eng.*, vol. 69, no. 1, pp. 63–74, 2022, doi: 10.1109/TBME.2021.3087137.
- [11] E. Sinopoulou *et al.*, "Chronic muscle recordings reveal recovery of forelimb function in spinal injured female rats after cortical epidural stimulation combined with rehabilitation and chondroitinase ABC," *J. Neurosci. Res.*, vol. 100, no. 11, pp. 2055–2076, 2022, doi: 10.1002/jnr.25111.
- [12] M. A. Gorvet, J. M. Wakeling, D. M. Morgan, D. Hidalgo Segura, J. Avey-Arroyo, and M. T. Butcher, "Keep calm and hang on: EMG activation in the forelimb musculature of three-toed sloths (Bradypus variegatus)," J. Exp. Biol., vol. 223, 2020, DOI: 10.1242/jeb.218370.
- [13] D. Zealear, Y. Li, and S. Huang, "An implantable system for chronic in vivo electromyography," *J. Vis. Exp.*, vol. 2020, no. 158, pp. 1–10, 2020, DOI: 10.3791/60345.
- [14] B. Faenger *et al.*, "Comparison between intramuscular multichannel electrodes and supramysial multichannel electrodes via EMG measurements for potential use as larynx stimulation electrodes: In vivo animal analysis," *Sensors (Switzerland)*, vol. 19, no. 20, 2019, DOI: 10.3390/s19204477.
- [15] H. A. Dewald *et al.*, "Stable, three degree-of-freedom myoelectric prosthetic control via chronic bipolar intramuscular electrodes: A case study," *J. Neuroeng. Rehabil.*, vol. 16, no. 1, pp. 1–13, 2019, DOI: 10.1186/s12984-019-0607-8.
- [16] I. Topchiy, A. M. Fink, K. A. Maki, and M. W. Calik, "Validation of PiezoSleep Scoring Against EEG/EMG Sleep Scoring in Rats," *Nat. Sci. Sleep*, vol. 14, no. October, pp. 1877–1886, 2022, DOI: 10.2147/NSS.S381367.
- [17] G. Tagliabue et al., "Limitations of surface EMG estimate of

parasternal intercostal to infer neural respiratory drive," Respir. Physiol. Neurobiol., vol. 285, no. November 2020, p. 103572, 2021, DOI: 10.1016/j.resp.2020.103572.

- [18] X. Su, M. Cutinella, S. Koppes, J. E. Agran, and D. A. Dinsmoor, "Electromyographic Responses Across Different Pulse-Widths of Sacral Neuromodulation in Sheep," Neuromodulation, vol. 22, no. 6, pp. 684-689, 2019, DOI: 10.1111/ner.12779.
- [19] A. S. Nugroho, A. B. Witarto, and D. Handoko, "Application of Support Vector Machine in Bioinformatics," in Proceeding of Indonesian Scientific Meeting in Central Japan, 2003.
 [20] C. Cortes and V. Vapnik, "Support-Vector Networks," Mach. Learn.,
- vol. 20, pp. 273–297, 1995.
- [21] Z. Song, Y. Ren, and G. He, "Privacy-Preserving KNN Classification Algorithm for Smart Grid," Secure. Commun. Networks, vol. 2022, 2022, DOI: 10.1155/2022/7333175.
- [22] J. Liu, C. Wang, Z. Tu, X. A. Wang, C. Lin, and Z. Li, "Secure KNN

Classification Scheme Based on Homomorphic Encryption for Cyberspace," Secure. Commun. Networks, vol. 2021, 2021, DOI: 10.1155/2021/8759922.

- [23] D. Zhao et al., "k-means clustering and kNN classification based on negative databases," Appl. Soft Comput., vol. 110, p. 107732, 2021, DOI: 10.1016/j.asoc.2021.107732.
- [24] W. Xing and Y. Bei, "Medical Health Big Data Classification Based on KNN Classification Algorithm," *IEEE Access*, vol. 8, pp. 28808–28819, 2020, DOI: 10.1109/ACCESS.2019.2955754.
- [25] S. Zhang, "Challenges in KNN Classification," *IEEE Trans. Knowl. Data Eng.*, vol. 34, no. 10, pp. 4663–4675, 2021, DOI: 10.1109/TKDE.2021.3049250.







The 2023 International Conference on **Computer Science, Information Technology and Engineering**

Jakarta - Indonesia



CERTIFICATE OF PRESENTER

No. 59/BIIC/LPPM-BiU/II/2023

This is to certify that

Romy Budhi Widodo, Devina Trixie and Windra Swastika (Universitas Ma Chung, Indonesia)

has written the paper titled

Study of EMG-based Mouse Clicks Type Detection

at The 2023 International Conference on Computer Science, Information Technology and Engineering with theme "Digital Transformation Strategy in Facing the VUCA and TUNA Era" on 16 February 2023 in Jakarta, Indonesia







Sponsor:

Co-Host:









The 2023



International Conference on Computer Science, Information Technology & Engineering Jakarta - Indonesia, 16 February 2023

Digital Transformation Strategy in Facing the VUCA & TUNA Era

biic.binainsani.ac.id/ICCoSITE.html

The 2023 International Conference on Computer Science, Information Technology & Engineering IEEE Conference Record Number: #57641

ICCOSITE

Jakarta - Indonesia, 16 February 2023

https://biic.binainsani.ac.id/ICCoSITE.html

From The Rector

The honorable:

Dr. Samsuri (The Head of Higher Education Service Institution Region IV West Java and Banten as the representative of the Ministry of Education and Culture of Republic of Indonesia) All Plenary Speakers from Indonesia, Malaysia, Turkey and Saudi Arabia, and All Researchers and Reviewers Warmest Greetings from Bina Insani University. Ladies and Gentlemen.

At first, please allow me to commence this occasion by thanking Dr. Samsuri (the Head of Indonesian Higher Education Service Institution Region IV West Java and Banten) and Prof. Dr.rer.nat. Achmad Benny Mutiara, SSi, S.Kom (Chairman of APTIKOM) for their supports in order to make this international conference take place.

On behalf of Bina Insani University we welcome and thank the Honorable Plenary Speakers:

- Prof. Dr. Ramlee Mustapha from the Department of Engineering Technology, Faculty of Technical and Vocational Education, Sultan Idris Education University, Malaysia,
- Prof. Ir. Teddy Mantoro, M.Sc., Ph.D., SMIEEE from the Faculty of Science and Technology, Sampoerna University, Jakarta Chair of IEEE Computational Intelligence Society, Indonesia Chapter
- Prof. Dr. Ali Resül USUL from Anadolu University Vice Rectors, Turkey,
- Prof. Dr.rer.nat. Achmad Benny Mutiara, S.Si, S.Kom, Chairman of APTIKOM, Indonesia, and
- Prof. Ir. Anton Satria Prabuwono, S.T., S.Si., M.M., M.Sc., Ph.D., SMIEEE, SMACM from the Department of Information Technology Faculty of Computing & Information Technology in Rabigh King Abdulaziz University, Saudi Arabia.

The ICCoSITE 2023 delivers a prestigious international conference for researchers, educators, practitioners, and students throughout the world to present their most recent ideas, innovations and trends in the fields of Computer Science, Information Technology and Engineering.

The theme of ICCoSITE 2023 is Digital Transformation Strategy in Facing the VUCA and TUNA Era. Bina Insani University in cooperation with APTIKOM and IEEE Indonesia Section as Technical Sponsor would like to foster and to promote the works of all scholars in the ICCoSITE 2023. With a hope, we can develop science and technology for a much better future.

We also thank the paper reviewers and presenters for their hard works in the ICCoSITE 2023. Wish you all the best of luck in your endeavor in the ocean of science and technology.

Last but not least, we would also like to acknowledge and thank our Co Hosts: Universitas Indraprasta PGRI UNINDRA, Universitas Nasional, Pionir Perubahan, Institut Teknologi Garut ITG, Sekolah Tinggi Manajemen Informatika dan Komputer ROSMA, and Universitas Majalengka UNMA, Steering Committee, Organizing Committee and Reviewers Team, and all Participants to participate in The First Bina Insani International Conference on Computer Science, Information Technology and Engineering (ICCoSITE 2023). Thank you for the supports and assistances, shares and cares in the First Bina Insani International Conference. All the Best! May God bless us all.

Jakarta, 16 February 2023 Rector of Bina Insani University

Assoc. Prof. Dr. Indra Muis, S.S., M.M

From The Committee

The honorable:

All Steering Committee, All Plenary Speakers from Indonesia, Malaysia, Turkey and Saudi Arabia, and All Researchers and Reviewers Warmest Greetings from Bina Insani University. Ladies and Gentlemen.

Assalamualaikum Wr. Wb. I hope you are safe and health today.

Firstly, let us say thank you to almighty god for his blessings and grace, we can gather in this room together or in this time by virtual, although under the condition of COVID-19 Pandemic, we are still be given strength, health, and chance to be capable of participating in the 2023 ICCoSITE Conference. In this moment, I would like to welcome you to the 2023 ICCoSITE Conference, I apologize that this conference held virtually, because the COVID-19 Pandemic has not ended yet. However, we must do this conference very well.

Nevertheless, we never give up to this situation, hopefully, the enthusiasm of the research can convey the best things to all participants and can be seen from the numbers of research articles sent to us. Alhamdulillah, although we are still dealing with the pandemic, the enthusiasm of the researchers can be seen from the numbers of research articles submitted to us. We received **477 articles from 26 countries**. However **only 191 articles are accepted from 18 countries** in this conference. Its means, the acceptance ratio **is 40%**.

We feel so proud and grateful good participations of researches who have been willing to join their research results, for publishing in this International Conference, I would like to say thank you very much to the plenary speakers, The IEEE Indonesia Section, who have believed and given strong support to this conference from the beginning.

I personally hope for the next year, we could meet again warmly and join conferences from researchers. Ladies and gentlemen, this is the end of my speech, I would like to sincerely apologize for any inconveniences during this meeting. Thank you very much for your kind attention and Wassalamualaikum.

Jakarta, 16 February 2023 General Chair,

Ahmad Chusyairi, S.Kom., M.Kom.

The Committees

STEERING COMMITTEE

Prof. Ir. Gamantyo Hendrantoro, M.Eng., Ph.D.(IEEE Indonesia Section)Dr.-Ing.Wahyudi Hasbi, S.Si., M.Kom.(National Research & Innovation Agency (BRIN), Indonesia)Assoc. Prof. Dr. Indra Muis, S.S., M.M.(Universitas Bina Insani, Indonesia)Shalahuddin, S.Pd., M.M.(Universitas Bina Insani, Indonesia)Rita Wahyuni Arifin, S.Kom., M.Kom.(Universitas Bina Insani, Indonesia)Kristiana Widiawati, S.Pd., M.M., CMA.(Universitas Bina Insani, Indonesia)

ORGANIZING COMMITTEE

General Chair	
Ahmad Chusyairi	(Universitas Bina Insani, Indonesia)
Treasurer	
Lucia Ari Diyani	(Universitas Bina Insani, Indonesia)
Secretary	
Dwi Ismiyana Putri	(Universitas Bina Insani, Indonesia)
Program Chair	
Adrianus Trigunadi Santoso	(Universitas Bina Insani, Indonesia)
Chita Oktapriana	(Universitas Bina Insani, Indonesia)
Publication Chair	
Dade Nurdiniah	(Universitas Bina Insani, Indonesia)
Rully Pramudita	(Universitas Bina Insani, Indonesia)
Technical Team	
Jafar Shadiq	(Universitas Bina Insani, Indonesia)
Mardi Yudhi Putra	(Universitas Bina Insani, Indonesia)
Ari Nurul Alfian	(Universitas Bina Insani, Indonesia)

Technical Program Committees

Title	Name	Affliation	Country
Prof.	Luis Alves	Polytechnic Institute of Bragança	Portugal
Prof.	Saad Chakkor	University of Abdelmalek Essaâdi	Morocco
Prof.	George Dekoulis	Aerospace Engineering Institute	Cyprus
Prof.	Arif Djunaidy	Institut Teknologi Sepuluh Nopember	Indonesia
Prof.	Sri Hartati	Gadjah Mada University	Indonesia
Prof.	Mohammed Kaabar	Washington State University	USA
Prof.	Mustafa Man	University Malaysia Terengganu	Malaysia
Prof.	Mohammed Mohammed	University of Technology, Baghdad	Iraq
Prof.	Nurdin Nurdin	Universitas Islam Negeri Datokarama Palu	Indonesia
Prof.	Grienggrai Rajchakit	Maejo University	Thailand
Prof.	Priya Ranjan	Bhuvaneshvar Institute of Technology	India
Prof.	Sayantam Sarkar	MVJ College of Engineering	India
Prof.	Iickho Song	Korea Advanced Institute of Science and Technology	Korea (South)
Prof.	Yi-Jen Su	Shu-Te University	Taiwan
Prof.	Jeng-Feng Weng	NationalUnited University	Taiwan
Prof.	Thaweesak Yingthawornsuk	King Mongkut's University of Technology	Thailand
Prof.	Ali Zalzala	Thonburi Community Tracks Ltd	United Kingdom (Great Britain)
Dr.	Intan Ermahani A. Jalil	Universiti Teknikal Malaysia Melaka	Malaysia
Dr.	Zainul Abidin	Universitas Brawijaya	Indonesia
Dr.	Naveen Aggarwal	Panjab University	India
Dr.	Mohd Ashraf Ahmad	Universiti Malaysia Pahang	Malaysia
Dr.	Mohd Rosli Arshad	University Kuala Lumpur	Malaysia
Dr.	Hilmi Aulawi	Institut Teknologi Garut	Indonesia
Dr.	Asrul Izam Azmi	Universiti Teknologi Malaysia	Malaysia
Dr.	Alessandro Carrega	UNIGE	Italy
Dr.	Akaa Eteng	University of Port Harcourt	Nigeria
Dr.	Ahmad Fajar	Bina Nusantara University	Indonesia
Dr.	Akhil Gupta	Lovely Professional University	India
Dr.	Henderi Henderi	University of Raharja	Indonesia
Dr.	Fajar Hermawati	Universitas 17 Agustus 1945 Surabaya	Indonesia
Dr.	Ramkumar Jaganathan	Dr NGP Arts and Science College	India
Dr.	Lie Jasa	Udayana University	Indonesia
Dr.	Ahmed Kawther	Mustansiriyah Universtiy	Iraq
Dr.	Channa Khieng	National Polytechnic Institute of Cambodia	Cambodia
Dr.	Sandy Kosasi	STMIK Pontianak	Indonesia
Dr.	Dede Kurniadi	Institut Teknologi Garut	Indonesia

Dr.	Xia Li	Apple	USA
Dr.	Pavel Loskot	ZJU-UIUC Institute	China
Dr.	Maslin Masrom	UniversitiTeknologi Malaysia	Malaysia
Dr.	Ratheesh Kumar Meleppat	University of California Davis	USA
Dr.	Dan Milici	University of Suceava	Romania
Dr.	Nor Liyana Mohd Shuib	University of Malaya	Malaysia
Dr.	Hea Choon Ngo	Universiti Teknikal Malaysia Melaka	Malaysia
Dr.	Nitish Ojha	Sharda University, Greater Noida, UP	India
Dr.	Ilker Ali Ozkan	Selcuk University	Turkey
Dr.	Shashikant Patil	Mumbai University	India
Dr.	Kiran Sree Pokkuluri	Shri Vishnu Engineering College for	India
Dr.	Tri Priyambodo	Women(A) Universitas Gadjah Mada	Indonesia
Dr.	Ali Rafiei	University of Technology Sydney	Australia
Dr.	Zairi Ismael Rizman	Universiti Teknologi MARA	Malaysia
Dr.	Dedi Rohendi	Universitas Pendidikan Indonesia	Indonesia
Dr.	Heru Agus Santoso	Dian Nuswantoro University	Indonesia
Dr.	Enny Sela	Universitas Teknologi Yogyakarta	Indonesia
Dr.	Anindita Septiarini	Universitas Mulawarman	Indonesia
Dr.	Iwan Setyawan	Satya Wacana Christian University	Indonesia
Dr.	Aditi Sharma	Parul University, Vadodara	India
Dr.	Poorani Shivkumar	ESEC	India
Dr.	Neeraj Singh	LTTS	India
Dr.	Joey Suba	University of the Assumption	Philippines
Dr.	Chakib Taybi	Mohammed First University	Morocco
Dr.	Evi Triandini	Institut Teknologi dan Bisnis STIKOM Bali	Indonesia
Dr.	Tram Truong-Huu	Agency for Science, Technology and Research (A*STAR)	Singapore
Dr.	Terlapu Vital	jntuK	India
Dr.	Widodo Widodo	Universitas Negeri Jakarta	Indonesia
Dr.	Beihao Xia	Huazhong University of Science and Technology	China
Dr.	Warusia Yassin	Universiti Teknikal Malaysia Melaka	Malaysia
Dr.	Nur Zareen Zulkarnain	Universiti Teknikal Malaysia Melaka	Malaysia
Mr.	I Adiyasa	Gadjah Mada University	Indonesia
Mr.	Yosua Alvin Adi Soetrisno	Diponegoro University	Indonesia
Mr.	Lala Hucadinota Ainul Amri	Politeknik Negeri Media Kreatif	Indonesia
Mr.	Abul Al Arabi	Texas A&M University	USA
Mr.	Andria Arisal	Indonesian Institute of Sciences	Indonesia
Mr.	Nanang Cahyana	Bandung Institute of Technology	Indonesia
Mr.	Voeun Chan	Institute of Technical	Cambodia
Mr.	Ahmad Chusyairi	Universitas Bina Insani	Indonesia
N.4	Andi Wahiy Dahardia Emanyal	Universitas Atma Java Vegyakarta	Indonasia

Mr.	Aashish Gadgil	KLS Gogte Institute of Technology, Belgaum	India
Mr.	Ibnu Hadi Purwanto	Universitas AMIKOM Yogyakarta	Indonesia
Mr.	Seng Hansun	Universitas Multimedia Nusantara	Indonesia
Mr.	Hanny Haryanto	Universitas Dian Nuswantoro	Indonesia
Mr.	Roberto Carlos Herrera Lara	National Polytechnic School	Ecuador
Mr.	M Heryanto	Universitas Dian Nuswantoro	Indonesia
Mr.	Hozairi Hozairi	Universitas Islam Madura	Indonesia
Mr.	Paulus Insap Santosa	Universitas Gadjah Mada	Indonesia
Mr.	Iswandi Iswandi	Gadjah Mada University	Indonesia
Mr.	Reza Khalilian	MUI Research Assistant and Author	Iran
Mr.	Beomseok Lee	Chung-Ang University	Korea (South)
Mr.	Muhammad Agung Nugroho	Universitas Teknologi Digital Indonesia	Indonesia
Mr.	Andrew Pakpahan	Jl. Kolonel Masturi No. 288	Indonesia
Mr.	Alvaro Paricio García	Universidad de Alcala	Spain
Mr.	Sutarman PhD	Magister of Information Technology University Technoloy of Yogyakarta	Indonesia
Mr.	Irfan Pratama	Universitas Mercubuana Yogyakarta	Indonesia
Mr.	Edy Prayitno	Universitas Teknologi DIgital Indonesia	Indonesia
Mr.	Rasim Rasim	Indonesia University of Education	Indonesia
Mr.	Bayu Setiaji	Universitas AMIKOM Yogyakarta	Indonesia
Mr.	Karthik Sivarama Krishnan	Rochester Institute of Technology	USA
Mr.	Suharjito Suharjito	Bina Nusantara University	Indonesia
Mr.	Cucut Susanto	Universitas Dipa Makassar	Indonesia
Ms.	Wasnaa Kadhim	University of Information Technology and Communications	Iraq
Ms.	Ni Wayan Septiani	Universitas Indraprasta PGRI Jakarta	Indonesia
Mrs.	Rita Arifin	Bina Insani University	Indonesia
Mrs.	Arna Fariza	Politeknik Elektronika Negeri Surabaya	Indonesia
Mrs.	Intan Mutia	IPB University	Indonesia
Mrs.	Dewi Tresnawati	Institut Teknologi Garut	Indonesia
Mrs.	Wihayati Wihayati	Satya Wacana Christian University	Indonesia

Detail Conference Program

2023 ICCoSITE Conference – Thursday, February 16, 2023 06:30 AM Jakarta (Time based: Jakarta, Indonesia GMT+7)

Join Zoom Meeting

https://zoom.us/j/93976814586?pwd=QVhzMDdOL2hUbUJKM3BvRks1WWRBdz09

Meeting ID : 939 7681 4586 Passcode : 2023

Start	m'	End	Agenda	Room
6:45	0:15	7:00	Preparing	Main Zoom
7:00	2:30	9:30	Parallel Session 1	9 Breakout Rooms
9:30	2:45	12:15	Opening Ceremony	Main Zoom
9:30	0:02	9:32	Greeting from MC	
9:32	0:04	9:36	Indonesia National Anthem	
9:36	0:04	9:40	Song of Bina Insani University	
9:40	0:05	9:45	Reporting Speech: Committee	
9:45	0:15	10:00	Speech from LLDIKTI IV	
10:00	0:05	10:05	Introduce moderator to Plenary Sessions	
10:05	0:05	10:10	Open for Plenary Session	
10:10	0:30	10:40	Speaker 1: Prof. Dr.rer.nat. Achmad Benny Mutiara, S.Si., S.Kom.	
10:40	0:30	11:10	Speaker 2: Prof. Ir. Teddy Mantoro, M.Sc., Ph.D., SM.IEEE	
11:10	0:30	11:40	Speaker 3: Prof. Dr. Ramlee Mustapha	
11:40	0:30	12:10	QnA	
12:10	0:05	12:15	Closing & Photo	
12:15	0:45	13:00	Break	
13:00	2:30	15:45	Parallel Session 2	9 Breakout Rooms
15:45	0:15	16:00	Break	Main Zoom
16:00	0:05	16:05	Open for Closing Session	
16:05	0:25	16:30	Speaker 4: Prof. Ir. Anton Satria Prabuwono, Ph.D., SMIEEE, SMACM	
16:30	0:25	16:55	Speaker 5: Prof. Dr. Ali Resül USUL	
16:55	0:25	17:20	Q n A	
17:20	0:10	17:30	Awarding Best Papers - Runner Up	
17:30	0:05	17:35	Photo Session & Closing	
17:35	0:05	17:40	Leave Zoom Meeting	

Table of Papers

Page	Paper Id	Paper Title
1	1570859071	Airport Runway Foreign Object Debris (FOD) Detection Based on YOLOX architecture
 2	1570870798	Mandalika Modeling Topic on Social Media Using Latent Dirichlet Allocation
3	1570871922	Visualizing Texture of Fractal Arts in Unity3D Framework
4	1570874756	Control of DC-Output Voltage for Two Level DC/DC Boost Converter by Sliding Mode Controller in Application of Fuel Cell
5	1570874935	Discord Bot Design for Hate Speech Sensor Using Convolutional Neural Networks (CNN) Method
6	1570875033	Spice Classification Using Histogram Of Oriented Gradient (HOG) Feature Extraction and K-Nearest Neighbor (K-NN) Method
7	1570875034	Spice Classification Using Speeded-Up Robust Features (SURF) Feature Extraction and Naïve Bayes Method
8	1570875035	In-House Facial Data Collection for Face Recognition Accuracy: Dataset Accuracy Analysis
9	1570876790	Exploratory Data Analysis And Predict Income Udemy Course Instructors Using Machine Learning Algorithm
10	1570878030	Hand Gesture Recognition For Tone Classification According To Kodaly Handsign Using CNN
11	1570870998	Improved VGG-16 for Classifying Thyroid Nodule Using Thyroid Ultrasound Images
12	1570873305	Public Sentiment Analysis of KOMINFO Data Leaking by Bjorka using Support Vector Machine
13	1570874713	Predicting Priority Time Patrol Using Triple ES and AHP
14	1570874742	Study of EMG-based Mouse Clicks Type Detection
15	1570874800	Sentiment Analysis of Hashtag Activism on Social Media Twitter
16	1570874975	Feature Extraction in Hierarchical Multi-Label Classification for Dangerous Speech Identification on Twitter Texts
17	1570874977	The effect of grooves on the in-wheel motor cover of an electric scooter to increase the heat transfer process
18	1570875002	Prediction Analysis Of Four Disease Risk Using Decision Tree C4.5
19	1570877746	Compensator Design for Power Loss Reduction on IGBT Switching
20	1570877974	Restaurant Customer Feedback Sentiment Analysis using Aspect Embedding Long Short-term Memory Model
21	1570871515	Reconstruction of simulated VLBI data using the SARA method and random raw patches
22	1570872185	Effect Difference Size of Tetrahedron Sun Tracker Based on Sensor for Energy Harvesting
23	1570873016	Model Reference Adaptive Control Design for CubeSat with Magnetorquer
24	1570874812	The Influence Factors of Short Video Advertising in Social Electronic Commerce Shop Based on Customer Brand Engagement Model
25	1570874826	The effectiveness of social media (TikTok) in improving buying decisions in millennials

14

1570874742 - 1.2

Study of EMG-based Mouse Clicks Type Detection

Romy Budhi Widodo, Devina Trixie and Windra Swastika (Universitas Ma Chung, Indonesia)

romy_budhi@yahoo.com

Abstract

Keyword

EMG; K- Nearest Neighbor; Support Vector Machine; Classification	The operation of a computer requires humans to use several parts of their body. However, there are some conditions where humans cannot operate computers correctly or in a normal position; examples of these conditions are accident victims and people with disabilities. Therefore, a system is needed to help make it easier for these people to operate the computer. This study will create a system that can classify click types using EMG sensors, the K-NN method, and the SVM method. EMG sensors help take data in the form of signals from human muscle contractions which will later be classified into left-click and right-click. Data from EMG sensors will be trained using the K-NN and SVM
	methods using 54 data sets in each class, namely left-click and right- click classes. The K-NN method will be trained using k=3, 5, 7, 9, and 11. The SVM method uses linear kernels, Radial Basis Function (RBF), polynomials, and sigmoids. After that, the accuracy values of the two methods will be compared. The study has successfully classified the types of clicks based on the input from the EMG sensor using the K-NN method with the highest accuracy results using k = 3, which is 81.81%, and the SVM method using polynomial kernels which are 84.84%. The highest accuracy value was obtained by comparing the two methods, namely using the polynomial kernel SVM method. Adding datasets and conducting experiments using other methods as further comparisons can be used to improve system accuracy.